

SPECIFICATION GUIDE

| | |
|-----------------------------------|---|
| Trade Name: | Edgeline® |
| Species: | Radiata pine (<i>Pinus radiata</i>) |
| Origin: | New Zealand |
| Sustainability: | FSC® mix, CoC No. SGSJK-COC-500007 |
| Density: | 450-500kg / m ³ seasoned |
| Moisture Content: | Kiln-dried to approx. 12% (+/- 3%) |
| Fire Hazard: | Group 3 |
| Preservative Treatment: | Untreated |
| Formaldehyde Emissions: | <0.15mg/L (Super E0) |
| VOC Status: | No other volatile organic compounds |
| Finger Jointing: | Glued with VOC- and formaldehyde-free single component polyurethane adhesive |
| Coatings: | Finished with one coat of Gesso primer and one coat of water based acrylic primer. Will accept most oil and water based film forming coating systems |
| Intended Use: | Highly suited to installation in sheltered indoor locations protected from termite and fungal decay hazards. Should not be used in exterior applications, including under verandahs, patios and eaves |
| Finishing Recommendations: | Fill nail holes and wipe down surfaces to remove sawdust, dirt and other contaminants. Apply two coats of premium acrylic or enamel topcoat to clean and dry timber |
| In-Service Performance: | Will expand and contract with seasonal variations in moisture and humidity levels. Not recommended for areas that receive frequent wetting, such as in shower cubicles or bathroom splashbacks |
| Manufacturer's Warranty: | 5 years against defects in materials and workmanship |